

Product name	Confidentiality level
E3372s	CONFIDENTIAL
Product version	Total 6 pages
V1.0	

# E3372s Firmware Release Notes

## V1.0

Prepared by	E3372 Team	Date	2014-5-22
Reviewed by	E3372 Team	Date	2014-5-22



Huawei Technologies Co., Ltd.

All rights reserved

## Revision Record

Date	Revision version	change Description	Author
2014-5-22	1.00	init	E3372 Team

# Table of Contents

1	Main Features .....	4
2	Hardware.....	4
2.1	<b>Hardware Specifications</b> .....	4
3	Firmware .....	5
3.1	<b>Version Description</b> .....	5
3.2	<b>Firmware Specifications</b> .....	5
3.3	<b>Improvement in the Previous Version</b> .....	6
3.4	<b>Known Limitations and Issues</b> .....	6



# E3372s Firmware Release Notes V1.0

## 1 Main Features

The E3372s supports the following standards:

- LTE cat4 data service up to 150Mbit/s (Downlink) and 50Mbit/s(Uplink)
- DC-HSPA+ data service up to 43.2 Mbit/s
- HSPA+ data service up to 21.6 Mbit/s
- HSDPA packet data service of up to 14.4 Mbit/s
- HSUPA data service up to 5.76 Mbit/s
- WCDMA PS domain data service of up to 384 Kbit/s
- Equalizer and receive diversity
- microSD Card Slot (Up to 32G)
- Data and SMS Service
- Plug and play
- Standard USB interface
- CSFB

## 2 Hardware

### 2.1 Hardware Specifications

Item	Specifications
Hardware Version	<ul style="list-style-type: none"><li>● CL1E3372SM</li></ul>
Technical standard	<ul style="list-style-type: none"><li>● LTE 3GPP R9</li><li>● HSPA+/UMTS: 3GPP R99/R5/R6/R7/R8</li><li>● GSM/GPRS/EDGE: 3GPP R99</li></ul>
External interfaces	USB: Type A with standard USB 2.0 High speed interface
	LED: indicating the status of the Data Card
	SD card: standard TF card interface
	SIM/USIM card: standard 6-pin SIM card interface
	RF interface: external RF interface
Maximum power consumption	≤ 3.5 W
Power supply	5V
Dimensions (D × W × H)	About 92mm(D) × 32mm(W) × 14mm (H)
Weight	≤ 50 g



Item	Specifications
Temperature	<ul style="list-style-type: none"> <li>Operating: -10°C to +40°C</li> <li>Storage: -20°C to +70°C</li> </ul>
Humidity	5% to 95%
Base Information	<ul style="list-style-type: none"> <li>Plug and play (PnP)</li> </ul>
	<ul style="list-style-type: none"> <li>Standard USB 2.0 High Speed interface, auto installation, convenient for use</li> </ul>
<p><b>Note:</b>            3GPP = The 3rd Generation Partnership Project            TS = Technical Specification            LED = Light-Emitting Diode            SIM = Subscriber Identity Module            USIM = UMTS Subscriber Identity Module</p>	

### 3 Firmware

#### 3.1 Version Description

Firmware Version:	21.286.03.00.264
Baseline information	Balong V7R2 C30B286

#### 3.2 Firmware Specifications

Firmware		
Item	Specifications	
Version	21.286.03.00.264	
Information	Platform	Balong V7R2
	Baseline	C30B286
	Feature	LTE Supported
Data service	GSM CS domain	<ul style="list-style-type: none"> <li>Uplink: 9.6/14.4 kbit/s</li> <li>Downlink: 9.6/14.4 kbit/s</li> </ul>
	GPRS	<ul style="list-style-type: none"> <li>Uplink: 85.6 kbit/s</li> <li>Downlink: 85.6 kbit/s</li> </ul>
	EDGE	<ul style="list-style-type: none"> <li>Uplink: 236.8 kbit/s</li> <li>Downlink: 236.8 kbit/s</li> </ul>
	UMTS PS domain	<ul style="list-style-type: none"> <li>Uplink: 384 kbit/s</li> <li>Downlink: 384 kbit/s</li> </ul>
	HSDPA	<ul style="list-style-type: none"> <li>14.4Mbit/s</li> </ul>
	HSUPA	<ul style="list-style-type: none"> <li>5.76 Mbit/s</li> </ul>



Firmware		
Item	Specifications	
	HSPA+	<ul style="list-style-type: none"><li>• 21.6Mbit/s</li></ul>
	DC HSPA+	<ul style="list-style-type: none"><li>• Uplink:5.76 Mbit/s</li><li>• Downlink:43.2Mbit/s</li></ul>
	LTE FDD	<ul style="list-style-type: none"><li>• Uplink: 50Mbit/s</li><li>• Downlink:150Mbit/s</li></ul>
SMS	<ul style="list-style-type: none"><li>• SMS over SGs</li></ul>	
Operating System	<ul style="list-style-type: none"><li>• Windows XP/Windows Vista/WIN 7/MAC/WIN8</li></ul>	

### 3.3 Improvement in the Previous Version

Index	Case ID	Issue Description

### 3.4 Known Limitations and Issues

Index	Case ID	Issue Description