

| | |
|-----------------|-----------------------|
| Product name | Confidentiality level |
| E3272s | CONFIDENTIAL |
| Product version | Total 6 pages |
| V1.0 | |

E3272s HiLink Firmware Release Notes

V1.0

| | | | |
|-------------|------------------|------|----------|
| Prepared by | Qixiang 81005262 | Date | 2014-6-6 |
| Reviewed by | Qixiang 81005262 | Date | 2014-6-6 |
| Approved by | | Date | |



Huawei Technologies Co., Ltd.

All rights reserved

Revision Record

| Date | Revision version | FW Version | Change Description | Author |
|----------|------------------|---------------------|--------------------|---------------------|
| 2014-6-6 | 1.0 | FW 22.470.07.00.883 | Initial | Qixiang 81005262 |

Table of Contents

| | | |
|-----|---|---|
| 1 | Main Features | 4 |
| 2 | Hardware..... | 4 |
| 2.1 | Hardware Specifications | 4 |
| 3 | Firmware | 5 |
| 3.1 | Version Description | 5 |
| 3.2 | Firmware Specifications | 5 |
| 3.3 | Improvement in the Previous Version | 6 |
| 3.4 | Known Limitations and Issues | 6 |



E3272s Firmware Release Notes V1.0

1 Main Features

The E3272s supports the following standards:

- LTE data service up to 130Mbit/s(Downlink) and 50Mbit/s(Uplink)
- DC-HSPA+ data service up to 43.2 Mbit/s
- HSPA+ data service up to 21.6 Mbit/s
- HSDPA packet data service of up to 14.4 Mbit/s
- HSUPA data service up to 5.76 Mbit/s
- WCDMA PS domain data service of up to 384 Kbit/s
- Equalizer and receive diversity
- microSD Card Slot (Up to 32G)
- Data and SMS Service
- HiLink features (Driverless, WEB UI, Auto connect)
- Plug and play
- Standard USB interface

2 Hardware

2.1 Hardware Specifications

| Item | Specifications |
|---------------------------|--|
| Hardware Version | <ul style="list-style-type: none">● CH1E3272SM |
| Technical standard | <ul style="list-style-type: none">● LTE 3GPP R9● HSPA+/UMTS: 3GPP R99/R5/R6/R7/R8● GSM/GPRS/EDGE: 3GPP R99 |
| External interfaces | USB: Type A with standard USB 2.0 High speed interface |
| | LED: indicating the status of the Data Card |
| | SD card: standard TF card interface |
| | SIM/USIM card: standard 6-pin SIM card interface |
| | RF interface: external RF interface |
| Maximum power consumption | ≤ 3.5 W |
| Power supply | 5V |
| Dimensions (D × W × H) | About 92mm(D) × 32mm(W) × 14mm (H) |
| Weight | ≤ 50 g |



| Item | Specifications |
|---|--|
| Temperature | <ul style="list-style-type: none">Operating: -10°C to +40°CStorage: -20°C to +70°C |
| Humidity | 5% to 95% |
| Base Information | <ul style="list-style-type: none">Plug and play (PnP) |
| | <ul style="list-style-type: none">Standard USB 2.0 High Speed interface, auto installation, convenient for use |
| Note: 3GPP = The 3rd Generation Partnership Project TS = Technical Specification LED = Light-Emitting Diode SIM = Subscriber Identity Module USIM = UMTS Subscriber Identity Module | |
| | |

3 Firmware

3.1 Version Description

| | |
|----------------------|---------------------|
| Firmware Version: | 22.470.07.00.883 |
| Baseline information | Balong V7R1 C35B270 |

3.2 Firmware Specifications

| Firmware | | |
|--------------|------------------|---|
| Item | Specifications | |
| Version | 22.470.07.00.883 | |
| Information | Platform | Balong V7R1 |
| | Baseline | B270 |
| | Feature | LTE Supported |
| Data service | GSM CS domain | <ul style="list-style-type: none">Uplink: 9.6/14.4 kbit/sDownlink: 9.6/14.4 kbit/s |
| | GPRS | <ul style="list-style-type: none">Uplink: 85.6 kbit/sDownlink: 85.6 kbit/s |
| | EDGE | <ul style="list-style-type: none">Uplink: 236.8 kbit/sDownlink: 236.8 kbit/s |
| | UMTS PS domain | <ul style="list-style-type: none">Uplink: 384 kbit/sDownlink: 384 kbit/s |
| | HSDPA | <ul style="list-style-type: none">14.4Mbit/s |
| | HSUPA | <ul style="list-style-type: none">5.76 Mbit/s |



| Firmware | | |
|------------------|---|--|
| Item | Specifications | |
| | HSPA+ | <ul style="list-style-type: none">• 21.6Mbit/s |
| | DC HSPA+ | <ul style="list-style-type: none">• Uplink:5.76 Mbit/s• Downlink:43.2Mbit/s |
| | LTE | <ul style="list-style-type: none">• Uplink: 50Mbit/s• Downlink:130Mbit/s |
| SMS | <ul style="list-style-type: none">• SMS over SGs | |
| Operating System | <ul style="list-style-type: none">• Windows XP/Windows Vista/WIN 7/MAC/WIN8 | |

3.3 Improvement in the Previous Version

| Index | Case ID | Issue Description |
|-------|---------|--|
| 1 | | <ul style="list-style-type: none">• Fix issues |
| | | |

3.4 Known Limitations and Issues

| Index | Case ID | Issue Description |
|-------|---------|-------------------|
| | | |