

Product name	Confidentiality level
E3533	CONFIDENTIAL
Product version	Total 7 pages
V200R002	

E3533TCPU-V200R002B318D23SP00C105

Release Notes

Prepared by	Hanhaijun	Date	2014-01-03
Reviewed by		Date	
Approved by		Date	



Huawei Technologies Co., Ltd.

All rights reserved

Revision Record

Date	Revision version	FW-WebUI/HiLink Version	Change Description	Author
2014-01-03	1.0	FW V200R002B318D23SP00C105	Build 1.1 Version	Hanhaijun

Table of Contents

1	Main Features	4
2	Hardware.....	4
2.1	Version Description	4
2.2	Hardware Specifications	5
2.3	Improvements in the Previous Version	6
2.4	Known Limitations and Issues	6
3	Firmware	6
3.1	Version Description	6
3.2	Firmware Specifications	7
3.3	Improvement in the Previous Version	7
3.4	Known Limitations and Issues	7
4	WebUI/HiLink	7
4.1	Version Description	7
4.2	WebUI/HiLink Specifications	7

E3533s-2TCPU-V200R002B318D23SP00C105 Release Notes

Abbreviations	description
3GPP	The 3rd Generation Partnership Project
EDGE	Enhanced GPRS
LED	Light-emitting diode
SIM	Subscriber identity module
TS	Technical specification
USIM	UMTS subscriber identity module
MBIM	Mobile Broadband Interface Model

1 Main Features

The E3533s-2(W2100/W900) supports the following standards:

- HSPA+/HSDPA/HSUPA/WCDMA 2100/900/
and GSM/GPRS/EDGE 850/900/1800/1900 MHz
- HSPA+/HSDPA packet data service of up to 21.6 Mbit/s
- HSUPA packet data service of up to 5.76 Mbit/s
- WCDMA PS domain data service of up to 384 Kbit/s
- EDGE packet data service of up to 236.8 Kbit/s
- GPRS packet data service of up to 85.6 Kbit/s
- SMS based on CS/Packet Switched (PS) domain of GSM and WCDMA, supporting group sending of messages
- Plug and play (PnP)
- Standard USB interface, auto installation
- USB Stick, easy to connect
- HiLink features (Driverless, Zero installation, Auto connect)

2 Hardware

2.1 Version Description

Hardware Version:Ver.A

Platform & Chipset:

Balong V3R3

BB Hi6758

PMU Hi6561
RFIC Hi6361

2.2 Hardware Specifications

Item	Specifications
Technical standard	<ul style="list-style-type: none"> • HSPA+/HSDPA/ WCDMA R7 • HSUPA R6 • GSM/GPRS/EGPRS R99
Operating frequency	<p>HSPA+/HSDPA/HSUPA/ WCDMA 2100 MHz:</p> <ul style="list-style-type: none"> • Uplink: 1920–1980 MHz • Downlink: 2110–2170 MHz <p>HSPA+/HSDPA/HSUPA/ WCDMA 900 MHz:</p> <ul style="list-style-type: none"> • Uplink: 880–915 MHz • Downlink: 925–960 MHz <p>GSM/GPRS/EDGE 850 MHz:</p> <ul style="list-style-type: none"> • Uplink: 824–849 MHz • Downlink: 869–894 MHz <p>GSM/GPRS/EDGE 900 MHz:</p> <ul style="list-style-type: none"> • Uplink: 880–915 MHz • Downlink: 925–960 MHz <p>GSM/GPRS/EDGE 1800 MHz:</p> <ul style="list-style-type: none"> • Uplink: 1710–1785 MHz • Downlink: 1805–1880 MHz <p>GSM/GPRS/EDGE 1900 MHz:</p> <ul style="list-style-type: none"> • Uplink: 1850–1910 MHz • Downlink: 1930–1990 MHz
External interfaces	USB interface: USB 2.0 high-speed interface
	LED: indicating the status of the network
	SIM/USIM card: standard 6-pin SIM card interface
Maximum transmitter power	HSPA+/HSDPA/HSUPA/ WCDMA 2100/900MHz: +22 dBm (Power Class 3)
	GSM/GPRS 850/900 MHz: +33 dBm (Power Class 4)
	GSM/GPRS 1800 MHz/1900 MHz: +30 dBm (Power Class 1)
	EDGE 850/900MHz: +27 dBm (Power Class E2)
	EDGE 1800MHz/1900MHz: +26 dBm (Power Class E2)
Static receiver sensitivity	HSPA+/HSDPA/HSUPA/WCDMA 2100/900MHz: compliant with 3GPP TS 25.101 (R7)
	GSM/GPRS/EDGE 850/900/1800/1900 MHz: compliant with 3GPP TS 05.05 (R99)
Maximum power consumption	2.5W
Power supply	5 V/500 mA (USB interfaces)

Item	Specifications
Dimensions (D × W × H)	67.5*25.5*7.0mm
Weight	<30g
Note: 3GPP = The 3rd Generation Partnership Project EDGE = enhanced GPRS LED = light-emitting diode SIM = subscriber identity module TS = technical specification USIM = UMTS subscriber identity module	

2.3 Improvements in the Previous Version

Index	Case ID	Issue Description
NA		

2.4 Known Limitations and Issues

Index	Case ID	Issue Description
NA		

3 Firmware

3.1 Version Description

Firmware Version: 22.318.23.00.105
Baseline information Balong V3R3C10B180
Windows Driver Version Huawei Flash card 1.5.11.0

USB PID/VID:
Switch Before :
MBIM: 12D1/0x157D
No MBIM 12D1/0x1F01
Switch After: 12D1/14DB

Upgrade tools: 31.110.1.0



3.2 Firmware Specifications

Item	Specifications
1	NONE

3.3 Improvement in the Previous Version

Index	Case ID	Issue Description
1		Supports PNN/SPN
2		Customize operator name
3		Customize roaming alert box to choose

3.4 Known Limitations and Issues

Index	Case ID	Issue Description
NA		

4 WebUI/HiLink

4.1 Version Description

WebUI/HiLink Version: V100R005B100D05SP00C105

4.2 WebUI/HiLink Specifications

Item	Specifications
1	Prefer to 《WebUI-V100R005B100D03P00C03 Release Notes》