

Product name	Confidentiality level
E3533s-58	CONFIDENTIAL
Product version	Total 7 pages
V200R002	

E3533s-58TCPU-22.318.27.00.259

Release Notes

Prepared by	lijunlong	Date	2014-4-30
Reviewed by		Date	
Approved by		Date	



Huawei Technologies Co., Ltd.

All rights reserved

Revision Record

Date	Revision version	FW-WebUI/HiLink Version	Change Description	Author
2014-4-30	1.0	FW V200R002B318D27SP00C259	Build 1.1 Version	lijunlong

Table of Contents

1	Main Features	4
2	Hardware.....	4
2.1	Version Description	4
2.2	Hardware Specifications	5
2.3	Improvements in the Previous Version	6
2.4	Known Limitations and Issues	6
3	Firmware	6
3.1	Version Description	6
3.2	Firmware Specifications	7
3.3	Improvement in the Previous Version	7
3.4	Known Limitations and Issues	7

E3533s-58TCPU-22.318.27.00.259 Release Notes

Abbreviations	description
3GPP	The 3rd Generation Partnership Project
EDGE	Enhanced GPRS
LED	Light-emitting diode
SIM	Subscriber identity module
TS	Technical specification
USIM	UMTS subscriber identity module
MBIM	Mobile Broadband Interface Model

1 Main Features

The E3533s-58(W1900/W1700/W850) supports the following standards:

- HSPA+/HSDPA/HSUPA/WCDMA 1900/1700/850 and GSM/GPRS/EDGE 850/900/1800/1900 MHz
- HSPA+/HSDPA packet data service of up to 21.6 Mbit/s
- HSUPA packet data service of up to 5.76 Mbit/s
- WCDMA PS domain data service of up to 384 Kbit/s
- EDGE packet data service of up to 236.8 Kbit/s
- GPRS packet data service of up to 85.6 Kbit/s
- SMS based on CS/Packet Switched (PS) domain of GSM and WCDMA, supporting group sending of messages
- Plug and play (PnP)
- Standard USB interface, auto installation
- USB Stick, easy to connect
- HiLink features (Driverless, Zero installation, Auto connect)

2 Hardware

2.1 Version Description

Hardware Version:
CH1E3533SM
Platform & Chipset:
Balong V3R3
BB Hi6758
PMU Hi6561
RFIC Hi6361

2.2 Hardware Specifications

Item	Specifications
Technical standard	<ul style="list-style-type: none"> • HSPA+/HSDPA/ WCDMA R7 • HSUPA R6 • GSM/GPRS/EGPRS R99
Operating frequency	<p>HSPA+/HSDPA/HSUPA/ WCDMA 1900 MHz:</p> <ul style="list-style-type: none"> • Uplink: 1850–1910 MHz • Downlink: 1930–1990 MHz <p>HSPA+/HSDPA/HSUPA/ WCDMA 1700 MHz(AWS)</p> <ul style="list-style-type: none"> • Uplink: 1710–1755MHz • Downlink: 2110–2155 MHz <p>HSPA+/HSDPA/HSUPA/ WCDMA 850 MHz</p> <ul style="list-style-type: none"> • Uplink: 824–849MHz • Downlink: 869–894 MHz <p>GSM/GPRS/EDGE 850 MHz:</p> <ul style="list-style-type: none"> • Uplink: 824–849 MHz • Downlink: 869–894 MHz <p>GSM/GPRS/EDGE 900 MHz:</p> <ul style="list-style-type: none"> • Uplink: 880–915 MHz • Downlink: 925–960 MHz <p>GSM/GPRS/EDGE 1800 MHz:</p> <ul style="list-style-type: none"> • Uplink: 1710–1785 MHz • Downlink: 1805–1880 MHz <p>GSM/GPRS/EDGE 1900 MHz:</p> <ul style="list-style-type: none"> • Uplink: 1850–1910 MHz • Downlink: 1930–1990 MHz
External interfaces	USB interface: USB 2.0 high-speed interface
	LED: indicating the status of the network
	SIM/USIM card: standard 6-pin SIM card interface
Maximum transmitter power	HSPA+/HSDPA/HSUPA/ WCDMA 1900/1700MHz: +22 dBm (Power Class 3)
	GSM/GPRS 850/900 MHz: +33 dBm (Power Class 4)
	GSM/GPRS 1800 MHz/1900 MHz: +30 dBm (Power Class 1)
	EDGE 850/900MHz: +27 dBm (Power Class E2)
	EDGE 1800MHz/1900MHz: +26 dBm (Power Class E2)
Static receiver sensitivity	HSPA+/HSDPA/HSUPA/WCDMA 2100/900MHz: compliant with 3GPP TS 25.101 (R7)
	GSM/GPRS/EDGE 850/900/1800/1900 MHz: compliant with 3GPP TS 05.05 (R99)
Maximum power consumption	2.5W
Power supply	5 V/500 mA (USB interfaces)

Item	Specifications
Dimensions (D × W × H)	67.5*25.5*7.0mm
Weight	<30g
Note: 3GPP = The 3rd Generation Partnership Project EDGE = enhanced GPRS LED = light-emitting diode SIM = subscriber identity module TS = technical specification USIM = UMTS subscriber identity module	

2.3 Improvements in the Previous Version

Index	Case ID	Issue Description
NA		

2.4 Known Limitations and Issues

Index	Case ID	Issue Description
NA		

3 Firmware

3.1 Version Description

Firmware Version: 22.318.27.00.259
Baseline information Balong V3R3C10B180
Windows Driver Version Huawei Flashcard 1.5.8.0

USB PID/VID:
Switch Before :
MBIM: 12D1/0x157D
No MBIM 12D1/0x1F01
Switch After: 12D1/14DB

Upgrade tools: 31.110.1.0

3.2 Firmware Specifications

Item	Specifications
1	NONE

3.3 Improvement in the Previous Version

Index	Case ID	Issue Description
1		Close MBIM function

3.4 Known Limitations and Issues

Index	Case ID	Issue Description
NA		