

Product name	Confidentiality level
E3372h-607	CONFIDENTIAL
Product version	Total 6 pages
V1.0	

E3372h Firmware Release Notes

V1.0

Prepared by	Huwuming	Date	2014-11-19
Reviewed by	Xujun,liuzhenbo	Date	2014-11-19
Approved by		Date	



Huawei Technologies Co., Ltd.

All rights reserved

Revision Record

Date	Revision version	FW-WebUI/Stick Version	Change Description	Author
2014-11-19	1.0	FW 21.110.99.02.00.00	First version	Huwuming

Table of Contents

1	Main Features	4
2	Hardware.....	4
2.1	Hardware Specifications	4
3	Firmware	5
3.1	Version Description	5
3.2	Firmware Specifications	5
3.3	Improvement in the Previous Version	6
3.4	Known Limitations and Issues	6



E3372h Firmware Release Notes V1.0

1 Main Features

The E3372h supports the following standards:

- LTE cat4 data service up to 150Mbit/s (Downlink) and 50Mbit/s(Uplink)
- DC-HSPA+ data service up to 43.2 Mbit/s
- HSPA+ data service up to 21.6 Mbit/s
- HSDPA packet data service of up to 14.4 Mbit/s
- HSUPA data service up to 5.76 Mbit/s
- WCDMA PS domain data service of up to 384 Kbit/s
- Equalizer and receive diversity
- microSD Card Slot (Up to 32G)
- Data and SMS Service
- Plug and play
- Standard USB interface
- CSFB

2 Hardware

2.1 Hardware Specifications

Item	Specifications
Hardware Version	<ul style="list-style-type: none">● CL2E3372HM
Technical standard	<ul style="list-style-type: none">● LTE 3GPP R9● HSPA+/UMTS: 3GPP R99/R5/R6/R7/R8● GSM/GPRS/EDGE: 3GPP R99
External interfaces	USB: Type A with standard USB 2.0 High speed interface
	LED: indicating the status of the Data Card
	SD card: standard TF card interface
	SIM/USIM card: standard 6-pin SIM card interface
	RF interface: external RF interface
Maximum power consumption	≤ 3.5 W
Power supply	5V
Dimensions (D × W × H)	About 88mm(D) × 28mm(W) × 11.5mm (H)
Weight	≤ 25 g



Item	Specifications
Temperature	<ul style="list-style-type: none">Operating: -10°C to +40°CStorage: -20°C to +70°C
Humidity	5% to 95%
Base Information	<ul style="list-style-type: none">Plug and play (PnP)
	<ul style="list-style-type: none">Standard USB 2.0 High Speed interface, auto installation, convenient for use
Note: 3GPP = The 3rd Generation Partnership Project TS = Technical Specification LED = Light-Emitting Diode SIM = Subscriber Identity Module USIM = UMTS Subscriber Identity Module	

3 Firmware

3.1 Version Description

Firmware Version:	21.110.99.02.00
Baseline information	Balong V7R11 C30B110

3.2 Firmware Specifications

Firmware		
Item	Specifications	
Version	21.110.99.02.00	
Information	Platform	Balong V7R11
	Baseline	C30B110
	Feature	LTE Supported
Data service	GSM CS domain	<ul style="list-style-type: none">Uplink: 9.6/14.4 kbit/sDownlink: 9.6/14.4 kbit/s
	GPRS	<ul style="list-style-type: none">Uplink: 85.6 kbit/sDownlink: 85.6 kbit/s
	EDGE	<ul style="list-style-type: none">Uplink: 236.8 kbit/sDownlink: 236.8 kbit/s
	UMTS PS domain	<ul style="list-style-type: none">Uplink: 384 kbit/sDownlink: 384 kbit/s
	HSDPA	<ul style="list-style-type: none">14.4Mbit/s
	HSUPA	<ul style="list-style-type: none">5.76 Mbit/s



Firmware		
Item	Specifications	
	HSPA+	<ul style="list-style-type: none">• 21.6Mbit/s
	DC HSPA+	<ul style="list-style-type: none">• Uplink:5.76 Mbit/s• Downlink:43.2Mbit/s
	LTE FDD	<ul style="list-style-type: none">• Uplink: 50Mbit/s• Downlink:150Mbit/s
SMS	<ul style="list-style-type: none">• SMS over SGs	
Operating System	<ul style="list-style-type: none">• Windows XP/Windows Vista/WIN 7/MAC/WIN8	

3.3 Improvement in the Previous Version

Index	Case ID	Issue Description

3.4 Known Limitations and Issues

Index	Case ID	Issue Description