

Product name	Confidentiality level
E5338	CONFIDENTIAL
Product version	Total 9 pages
V1.0	

HUAWEI E5338 Release Notes

V1.0

Prepared by	E5338 Team	Date	2014-09-20
Reviewed by	E5338Team	Date	2014-09-20
Approved by		Date	



Huawei Technologies Co., Ltd.

All rights reserved

Revision Record

Date	Revision version	FW-WebUI/HiLink Version	Change Description	Author
2014-08-04	1.0	FW 21.210.01.00.00 webUI 17.100.04.00.03	The 1 st Version	E5338Team
2014-08-22	2.0	FW 21.210.03.00.00 webUI 17.100.05.00.03	The 2 nd Version	E5338Team
2014-09-20	3.0	FW 21.210.05.00.00 webUI 17.100.05.00.03	The 3 nd Version	E5338Team
2014-11-28	4.0	FW 21.210.07.00.00 webUI 17.100.08.00.03	The 4 nd Version	E5338Team

Table of Contents

1	Main Features	4
2	Hardware.....	5
2.1	Version Description	5
2.2	Hardware Specifications	5
2.3	Version Description	7
2.4	Firmware Specifications	7
2.5	Improvement in the Previous Version	8
2.6	Known Limitations and Issues	8
3	WebUI.....	9
3.1	Version Description	9
3.2	WebUI Specifications	9
3.3	Improvement in the Previous Version	9
3.4	Known Limitations and Issue	9

HUAWEI E5338 Release Notes V1.0

Abbreviations	Description

1 Main Features

The E5338 mainly supports the following features:

- HSPA+ (DL) data service of up to 21.6 Mbit/s
- HSDPA (DL) data service of up to 14.4 Mbit/s
- HSUPA (UL) data service of up to 5.76 Mbit/s
- UMTS data service of up to 384 kbit/s
- EDGE data service of up to 236.8 kbit/s
- GPRS data service of up to 85.6 kbit/s
- PS domain data service based on UMTS and GSM
- SMS based on CS/PS domain of GSM and UMTS
- Wi-Fi
- Slim body
- Five-second fast boot
- Support for HUAWEI Mobile WiFi App
- Press and Play
- 3G/Wi-Fi auto offload
- IPv6 /IPv4 dual stack (optional)
- Built-in DHCP Server, DNS RELAY and NAT
- Online software upgrade
- Traffic statistic
- Standard Micro USB interface
- HiLink features (Driverless, Zero installation)
- LED indicators
- Built-in UMTS and WLAN high gain antenna
- Windows XP SP3, Windows Vista SP1/SP2, Windows 7, Windows 8, Windows 8.1 (does not support Windows RT), MAC OS X 10.7, 10.8 and 10.9 with latest upgrades

2 Hardware

2.1 Version Description

Hardware Version:	CH1E5338SM(E5338)
Platform & Chipset:	Balong Hi6758 &Realtek 8189

2.2 Hardware Specifications

Item	Specifications	
Technical standard	WAN: HSPA+/HSPA/UMTS/EDGE/GPRS/GSM	
	WLAN: IEEE 802.11b/g/n	
Operating frequency	HSPA+/HSPA/UMTS: B1(2100)/B2(1900)/B4(AWS)/B5(850)/B8(900) MHz	
	EDGE/GPRS/GSM: 1900/1800/900/850 MHz	
	WLAN: 2.4 GHz	
Internal memory	128 MB Flash, 64 MB Memory	
Maximum transmitter power	UMTS: 24 (+1/-3) dBm	
	WLAN	802.11b: 14 (+/-3) dBm
		802.11g: 11 (+/-3) dBm
		802.11n: 9 (+/-3) dBm
Receiver sensitivity	UMTS: Confirm to 3GPP Requirements	
	WLAN 802.11b	-76 dBm@11 Mbit/s
		-82 dBm@1 Mbit/s
	WLAN 802.11g: -65 dBm@54 Mbit/s	
	WLAN 802.11n: -64 dBm@65 Mbit/s	
WLAN speed	802.11b: Up to 11 Mbit/s	
	802.11g: Up to 54 Mbit/s	
	802.11n: Support MCS0–MCS7; Up to 72.2 Mbit/s.	
Maximum power consumption	3.5 W	
Power supply	AC: 100–240 V	
	DC: 5 V, 1 A	
Battery	Type: Li (rechargeable, irremovable)	
	Capacity: 3.7 V, 1500 mAh	

Item	Specifications	
	Maximum working time: 6 hours (depending on the network)	
	Maximum standby time: 300 hours (depending on the network)	
External interfaces	USB interface: Micro USB	
	SIM card interface: standard 6-pin micro SIM card interface	
Indicators	Signal	Green: Strong signal
		Orange: Weak signal
		Red: No signal
	Wi-Fi	Green: Wi-Fi turned on
		Blue: Connected to WLAN
	Battery	Green: Sufficient battery
		Blinking green: Charging the battery
		Red: Low battery
	Roaming	Green: Roaming
	Power	Blinks slowly: The Mobile WiFi enters the standby mode
Button	Power switch, Reset switch	
Antenna	<ul style="list-style-type: none"> Built-in GSM/UMTS main diversity antenna Built-in UMTS diversity antenna Built-in WLAN antenna 	
Dimensions (D × W × H)	98.4 mm×54.5 mm×6.8 mm	
Weight	about 67 g (including the battery)	
Temperature	Operating: 0℃ to +35℃	
	Storage: -20℃ to +60℃	
Humidity	5% to 95% (non-condensing)	

2.3 Version Description

Firmware Version: 21.210.07.00.00
Baseline information : BalongV300R300C50B210

2.4 Firmware Specifications

Item	Description
SMS	<ul style="list-style-type: none">• Writing/Sending/Receiving• Sending/Receiving extra-long messages• Storage: Up to 500 messages can be saved in the internal memory of the E5330Bs-2.• New message prompt
Network connection setup	<ul style="list-style-type: none">• APN management: create, delete and edit.• Set up network connection
WLAN setup	<ul style="list-style-type: none">• SSID broadcasting and hiding• Open system and shared key authentication• ASCII and HEX keys• 64/128-bit WEP encryption• 256-bit WPA-PSK and WPA2-PSK encryption• AES encryption algorithm• TKIP and AES integrated encryption algorithm• Automatic adjustment of ratios• Display STA status• Turn off Wi-Fi automatically• WLAN MAC filter
Firewall setup	<ul style="list-style-type: none">• Firewall Switch• LAN IP Filter• Virtual Server• ACL Service• DMZ Service• UPnP Service
NAT setup	CONE NAT Symmetric NAT ALG <ul style="list-style-type: none">• VPN passthrough

Item	Description
DHCP setup	<ul style="list-style-type: none"> DHCP server enabling and disabling Address pool of the DHCP server setup DHCP lease time setup
Software installation	Automatic installation (PnP)
3G/Wi-Fi auto offload	Accessing to WAN via 3G or Wi-Fi Automatic offload between 3G and Wi-Fi
IPv6/IPv4 dual stack (optional)	DHCPv6/v4 server and client DNSv6/v4 server and client Display IPv6/v4 WAN address
Other	Network connection settings: <ul style="list-style-type: none"> Automatic network selection and registration Manual network selection and registration
	Network status display: signal, operator name, system mode, and so on.
	Selection of network connection types, for example: <ul style="list-style-type: none"> 3G Only Auto
	PIN management: activate/deactivate PIN, PIN lock, changing PIN, unblocking by using the PUK.
System requirement	<ul style="list-style-type: none"> Windows XP SP3, Windows Vista SP1/SP2, Windows 7, Windows 8 (does not support Windows RT) Mac OS X 10.6, 10.7 and 10.8 with latest upgrades Your computer's hardware system should meet or exceed the recommended system requirements for the installed version of OS

2.5 Improvement in the Previous Version

Index	Case ID	Issue Description
NA		

2.6 Known Limitations and Issues

Index	Case ID	Issue Description
-------	---------	-------------------



NA		

3 WebUI

3.1 Version Description

WebUI Version:17.100.08.00.03

3.2 WebUI Specifications

Item	Specifications
NA	NA

3.3 Improvement in the Previous Version

Index	Case ID	Issue Description
NA		

3.4 Known Limitations and Issue

Index	Case ID	Issue Description
NA		