

Product name	Confidentiality level
E5383	CONFIDENTIAL
Product version	Total 7 pages
V1.0	

HUAWEI E5383TCPU-V200R001B298D99SP61C00

## Release Notes V1.0

Prepared by	宋富新/128588	Date	2014/11/14
Reviewed by	王竞47420 姚玉亮/168939	Date	2014/11/14
Approved by		Date	



Huawei Technologies Co., Ltd.

All rights reserved

## Revision Record

[illegible]

## Table of Contents

1 Main Features.....	4
2 Hardware .....	4
<b>2.1 Version Description .....</b>	<b>4</b>
<b>2.2 Hardware Specifications .....</b>	<b>4</b>
<b>2.3 Improvements in the Previous Version .....</b>	<b>5</b>
<b>2.4 Known Limitations and Issues .....</b>	<b>5</b>
3 Firmware .....	5
<b>3.1 Version Description .....</b>	<b>5</b>
<b>3.2 Firmware Specifications.....</b>	<b>6</b>
<b>3.3 Improvement in the Previous Version.....</b>	<b>6</b>
<b>3.4 Known Limitations and Issues .....</b>	<b>6</b>
4 WebUI/HiLink .....	6
<b>4.1 Version Description .....</b>	<b>6</b>
<b>4.2 WebUI/HiLink Specifications.....</b>	<b>6</b>
<b>4.3 Improvement in the Previous Version.....</b>	<b>7</b>
<b>4.4 Known Limitations and Issues .....</b>	<b>7</b>
<b>4.5 Version Description .....</b>	<b>7</b>
<b>4.6 Known Limitations and Issues .....</b>	<b>7</b>



# HUAWEI E5383TCPU-V200R001B298D99SP61C00 Release Notes

## V1.0

Abbreviations	Description

## 1 Main Features

The E5383 supports the following standards:

- LTE CAT6 DL/UL 300Mbps/50Mbps
- DC-HSPA+ data service up to 43.2 Mbit/s
- HSPA+ data service up to 21.6 Mbit/s
- HSDPA packet data service of up to 14.4 Mbit/s
- HSUPA data service up to 5.76 Mbit/s
- WCDMA PS domain data service of up to 384 Kbit/s
- Equalizer and receive diversity
- Plug and play
- Standard USB interface
- Support Windows XP/Windows 7/Windows 8/MAC...

## 2 Hardware

### 2.1 Version Description

Hardware Version:	CL1E5383SM Ver.A
Platform & Chipset:	Balong V700R002

### 2.2 Hardware Specifications

Item	Specifications	
Technical Standard	3GPP	R99/R5/R6/R7/R8/R9
	IEEE	802.11b/g/n 802.11a/n
Operating Frequency	B1 -1920-1980	B3- 1710-1785
	B21- 1447.9-1462.9	B19-830-845
Maximum Transmitter Power	LTE 22+/-2dbm W 23+1/-3dBm	
	GSM_LB:32dBm HB:29dBm	
Maximum Power Consumption	5W	
Memory	4G(NAND FLASH)+2G(LPDDR)	
WLAN Rate	150Mbps MAX	
External Interfaces	USB: Micro USB	



	LED: NA
	SIM/USIM card: Micro SIM
Display	LCD 2.4'
Keys	POWE KEY & TOUCH PANEL
Antenna	Internal
Static Receiver Sensitivity	B1: -97dBm B3: -94dBm B19: -97dBm B21: -97dBm
Power Supply	USB :4.75~5.25 / BAT :3.4~4.2
Battery	2400mAh
Dimensions (D × W × H)	90*56.7*13.5 mm
Weight	110G
Ambient Temperature	0~35℃
Humidity	5%~95%

## 2.3 Improvements in the Previous Version

Index	Case ID	Issue Description
Hardware Version		
Previous Hardware Version		NA
NA		

## 2.4 Known Limitations and Issues

Index	Case ID	Issue Description
NA		NA

# 3 Firmware

## 3.1 Version Description

Firmware Version:	21.298.99.61.00
Baseline information	Hi6930 V7R2



### 3.2 Firmware Specifications

Item	Specifications

### 3.3 Improvement in the Previous Version

Index	Case ID	Issue Description
Firmware Version		21.298.99.61.00
Previous Version	Firmware Version	21.298.99.60.00
1	New Features	
2		
3		

Index	Case ID	Issue Description
Firmware Version		
1	New Features	NA
2		
3		

### 3.4 Known Limitations and Issues

Index	Case ID	Issue Description
1	Unrealized Features	
2		
3		

## 4 WebUI/HiLink

### 4.1 Version Description

WebUI/HiLink Version: NA

### 4.2 WebUI/HiLink Specifications

Item	Specifications



Item	Specifications

#### 4.3 Improvement in the Previous Version

Index	Case ID	Issue Description
WebUI Version		
Previous WebUI Version		
1	New Features	
2		
3		

Index	Case ID	Issue Description
WebUI Version		
1	New Features	
2		
3		

#### 4.4 Known Limitations and Issues

Index	Case ID	Issue Description
1	Unrealized Features	
2		
3		

#### 4.5 Version Description

Accessory Product Version:

#### 4.6 Known Limitations and Issues