

| | |
|-----------------|-----------------------|
| Product name | Confidentiality level |
| E5573Bs-320 | CONFIDENTIAL |
| Product version | Total 6 pages |
| V3.0 | |

HUAWEI E5573Bs-320TCPU-V200R001B323D11SP00C547

Release Notes V1.0

| | | | |
|-------------|------------------|------|----------|
| Prepared by | E5573Bs-320 Team | Date | 2017/4/6 |
| Reviewed by | E5573Bs-320 Team | Date | 2017/4/6 |
| Approved by | E5573Bs-320 Team | Date | 2017/4/6 |



Huawei Technologies Co., Ltd.



Revision Record

| Date | Revision version | FW-WebUI/HiLink Version | Change Description | Author |
|----------|------------------|-------------------------|-----------------------------|-----------------|
| 2017/4/6 | 1.0 | FW 21.323.11.00.547 | The 1 st Version | E5573B-320 Team |

Table of Contents

| | | |
|-----|--|---|
| 1 | Main Features | 4 |
| 2 | Hardware | 4 |
| 2.1 | Version Description | 4 |
| 2.2 | Hardware Specifications | 4 |
| 2.3 | Improvements in the Previous Version | 5 |
| 2.4 | Known Limitations and Issues | 5 |
| 3 | Firmware | 5 |
| 3.1 | Version Description | 5 |
| 3.2 | Firmware Specifications | 6 |
| 3.3 | Improvement in the Previous Version (21.316.03.00.547) | 7 |
| 3.4 | Known Limitations and Issues | 7 |
| 4 | Software Vulnerabilities Fixes | 7 |



HUAWEI E5573Bs-320TCPU-V200R001B323D11SP00C547 Release Notes V1.0

| Abbreviations | Description |
|---------------|-------------|
| | |
| | |

1 Main Features

The E5573Bs-320 supports the following features:

- *LTE cat4 data service up to 150Mbit/s (Downlink) and 50Mbit/s(Uplink)*
- *DC-HSPA+ data service up to 43.2 Mbit/s*
- *HSPA+ data service up to 21.6 Mbit/s*
- *HSDPA packet data service of up to 14.4 Mbit/s*
- *HSUPA data service up to 5.76 Mbit/s*
- *WCDMA PS domain data service of up to 384 Kbit/s*
- *Equalizer and receive diversity*
- *Data and SMS Service*
- *WEB UI, Auto connect*
- *Plug and play*
- *Standard USB2.0*
- *Support WiFi 2.4GHz/5GHz*

2 Hardware

2.1 Version Description

| | |
|---------------------|--|
| Hardware Version: | CL1E5573SM10 Ver.A |
| Platform & Chipset: | Balong Hi6921 V7R11M, Broadcomm 43241 |

2.2 Hardware Specifications

| Item | Specifications | |
|---------------------------|---|------------------------|
| Technical Standard | 3GPP | R99/R5/R6/R7/R8/R9 |
| | IEEE | 802.11b/g/n |
| Operating Frequency | LTE | FDD B1,B3,B5,B7,B8,B20 |
| | UMTS | B1, B5,B8 |
| | EDGE/GPRS/GSM | 1900/1800/900/850 MHz |
| Maximum Transmitter Power | LTE | +23dBm (Class 3) |
| | UMTS | +24dBm (Class 3) |
| Maximum Power Consumption | 3.5W | |
| Memory | 128M NAND Flash, 128M DDR | |
| WLAN Rate | 802.11b: 11Mbit/s, 5.5Mbit/s, 2Mbit/s, 1Mbit/s 802.11g: 54Mbit/s, 48Mbit/s, 36Mbit/s, 24Mbit/s, 18Mbit/s, 12Mbit/s, 9Mbit/s, 6Mbit/s 802.11n: MCS0-MCS7(WiFi 1x1), MCS0-MCS15(WiFi 2x2) | |



| | |
|-----------------------------|--|
| External Interfaces | USB: Standard USB2.0 |
| | LED |
| | SIM/USIM card: 6pin, 1.8/3V |
| Display | LED |
| Keys | 1 Power, 1 Reset |
| Antenna | Internal |
| Static Receiver Sensitivity | Compliant with 3GPP TS 36.101(R9) for LTE, TS 25.101(R8) for UMTS. |
| Battery | 1500mAh |
| Dimensions (D × W × H) | 96.8*58*12.8 mm |
| Weight | <120g(include Battery) |
| Ambient Temperature | 0-35°C |
| Humidity | 5%-95% |

2.3 Improvements in the Previous Version

| Index | Case ID | Issue Description |
|---------------------------|---------|--------------------|
| Hardware Version | | CL1E5573SM01 Ver.A |
| Previous Hardware Version | | NA |
| NA | | |

2.4 Known Limitations and Issues

| Index | Case ID | Issue Description |
|-------|---------|-------------------|
| NA | | NA |

3 Firmware

3.1 Version Description

| | |
|----------------------|------------------|
| Firmware Version: | 21.323.11.00.547 |
| Baseline information | Hi6921 V7R11M |

3.2 Firmware Specifications

| Item | Specifications |
|---------------------|---|
| Login In | IP:192.168.8.1 Username:admin Userpassword:admin |
| WLAN parameters | SSID: HUAWEI-****, **** is the last four digits of MAC WIFI KEY : 8 random value |
| WEB Lanuage | Default:[Italian] Language:[English][Italian] |
| Dial up mode | Use "Connect/Disconnect" button instead of data switch. And add "Manual " mode, Manual mode as default. |
| Data roaming | Enable |
| Roaming prompt | When click "Connect" button under roaming, PLS pop up box to display below prompt: Italian: ATTENZIONE: la navigazione è passata sotto copertura GPRS, i costi di connessione sono più alti rispetto alla normale navigazione in copertura UMTS. English: WARNING: navigation has gone undercover GPRS connection costs are higher than navigating in UMTS. |
| Network mode | Need to display detail network mode in WEBUI like LTE/DC-HSPA+/HSPA+/HSPA/HSDPA/HSUPA/WCDMA/EDGE/GPRS/GSM |
| My number | Delete "My number" from WEBUI page |
| Network search mode | Display detail network search mode like Auto, 4G only, 3G only, 2G only |
| Change string | Change webui string |
| Power off button | Remove power off button from home page |
| 双IMSI Dual IMSI | 支持双IMSI 切换 Support Dual IMSI switch |

| Item | Specifications |
|------|---|
| APN | The APN For PLMN 22801: Associate with firmware, parameters adapted according PLMN+GID1, GID1=D8 |

3.3 Improvement in the Previous Version

| Index | Case ID | Issue Description |
|----------------------------------|-------------|---|
| Firmware Version | | 21.323.11.00.547 |
| Previous Firmware Version | | 21.316.03.00.547 |
| 1 | IMSI switch | Support Dual IMSI switch |
| 2 | apn | The APN For PLMN 22801:Associate with firmware, parameters adapted according PLMN+GID1. |
| 3 | apn | Add new apn |
| | | |
| | | |

3.4 Known Limitations and Issues

| Index | Case ID | Issue Description |
|-------|---------|-------------------|
| | | |
| | | |
| | | |

4 Software Vulnerabilities Fixes

| Software/Module name | Version | CVE ID | Vulnerability Description | Solution |
|----------------------|---------|--------|---------------------------|---|
| NA | NA | NA | NA | This version is not related to vulnerabilities fixes. |